

MATERIAL SAFETY DATA SHEET

BIRCHWOOD CASEY®
RIG® UNIVERSAL GREASE
(Grease used for UNIVERSAL GREASE APPLICATOR)

Page 1 of 4
DATE REVISED: 6/1/10
REVISION MSDS NO. 1

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: UNIVERSAL GREASE APPLICATOR
PRODUCT PART NUMBERS: 30002, RGA RIG®-RAG
MANUFACTURED BY: BIRCHWOOD LABORATORIES, INCORPORATED
7900 Fuller Road
Eden Prairie, MN 55344 USA
Product Information Telephone Number: (952) 937-7900 (8:00-4:00pm CST)
Fax Number: (952) 937-7979
www.birchwoodcasey.com

24 HOUR TRANSPORTATION EMERGENCY NUMBER: CHEMTREC 800-424-9300 U.S. & CANADA
703-527-3887 INTERNATIONAL (Collect)
24 HOUR POISON CONTROL EMERGENCY NUMBER: 866-291-7152 U.S. & CANADA

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: May be irritating to the skin, eyes.
APPEARANCE/ODOR: Yellow soft grease. Petroleum odor.
EYE CONTACT: May cause irritation.
SKIN CONTACT: May cause slight irritation with brief contact.
INGESTION: May cause abdominal discomfort, nausea and diarrhea.
INHALATION: No data available. However, inhalation is not an expected route of exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Table with 7 columns: Description, CAS #, Weight %, OSHA PEL* TWA, OSHA PEL STEL/C, ACGIH TLV TWA, ACGIH TLV STEL/C. Rows include Petrolatum, Sodium Alkyl Aryl Sulfonate, Solvent Refined, Hydrotreated Middle Distillate, and Hydrotreated Light Naphthentic Distillate.

TWA – Time-weighted Average STEL – Short-term exposure limit C – Ceiling (skin) – skin designation means that harmful amounts may be absorbed through the skin
* Certain States enforce PELs that were in place in 1989, but were later removed by the U.S. Supreme Court. Check with your State OSHA to determine which PEL is enforced in your State.

NE = not established

4. FIRST AID MEASURES

EYE CONTACT: Flush immediately with clean water. Continue for at least 15 minutes. Seek medical attention if necessary.

SKIN CONTACT: Remove contaminated clothing to avoid prolonged contact. Wash affected areas with water. Seek medical attention if irritation develops.

INGESTION: Do not induce vomiting; however, if swallowed and symptoms develop, seek medical attention.

INHALATION: Not applicable.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: 450 °F **METHOD USED:** C.O.C.

FLAMMABLE LIMITS: LFL: NDA UFL: NDA

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide, water spray or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

FIRE & EXPLOSION HAZARDS: This material may burn, but will not ignite readily.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear approved SCBA and full turn-out gear.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear recommended protective equipment. Absorb spill with an absorbent material such as sawdust, vermiculite or sand and place material into a closed container. Prevent material from entering water systems or sewers.

Review current local, state and federal laws, codes, statutes, and regulations to determine appropriate agencies to be notified, and the conditions under which they are to be notified. (See Section 13 for waste disposal comments).

7. HANDLING AND STORAGE

HANDLING: Wear protective equipment when handling product. Keep out of the reach of children.

STORAGE: Do not store where temperature may exceed 120°F

8. EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use a NIOSH approved respirator (Full or half-face organic vapor/P95 cartridge type) if any of the occupational exposure limits in Section 3 may be exceeded.

EYE PROTECTION: safety glasses with side shields, or goggles

PROTECTIVE GLOVES / BODY PROTECTION: polyvinyl alcohol (PVA) or natural rubber

VENTILATION: Use general/dilution or local exhaust ventilation as needed to ensure that occupational exposure limits are not exceeded. Do not use in enclosed spaces.

OTHER PROTECTIVE EQUIPMENT: Eyewash

NOTE: All PPE should be selected on the basis of an exposure assessment performed by a competent person.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: NDA	SPECIFIC GRAVITY: (Water = 1): 0.9
VAPOR PRESSURE: NDA	VOLATILE BY VOLUME: < 1%
VAPOR DENSITY: NDA	EVAPORATION RATE: NDA
SOLUBILITY IN WATER: Nil	pH: NDA
APPEARANCE: Yellow soft grease	ODOR: Petroleum odor

10. STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

INCOMPATIBILITY (materials to avoid): Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce carbon monoxide, metallic oxides and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

There is no product based toxicological information for this product. Toxicology information is provided for ingredients.

Oral LD₅₀: >5 g/kg (rat)

Carcinogenicity: IARC: None NTP: None OSHA: None

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NDA

ENVIRONMENTAL FATE: NDA

13. DISPOSAL CONSIDERATIONS

If discarded, this material and containers should be treated as hazardous wastes based on the characteristic of ignitability as defined under federal RCRA regulations (40 CFR 261). Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be dealt with by a licensed facility or waste hauler.

14. TRANSPORT INFORMATION

D.O.T. HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME:

Not regulated.

15. REGULATORY INFORMATION

TSCA (TOXIC SUBSTANCES CONTROL ACT): the materials in this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Response compensation and Liability Act, 40 CFR 117, 302: Reportable Quantities: NDA

SARA TITLE III (Superfund Amendments and Authorization Act):

Section 311/312:

Immediate Health Effects: Yes

Delayed Health Effects: Yes

Fire Hazard: No

Sudden Release of Pressure Hazard: No

Reactivity Hazard: No

Section 313 Reportable Ingredients: None

STATE "RIGHT-TO-KNOW": This product may contain components cited on certain state lists. Consult with your individual State regarding this product's components.

16. OTHER INFORMATION

National Fire Protection Association (NFPA): Health: 1 Flammability: 1 Reactivity: 0

The data here is for hazard communication to our employees, our customers and their employees, and authorized regulatory agencies. For the intended purpose, this MSDS (Material Safety data Sheet) may be duplicated or the data transcribed to an alternative form.

NOTE: The information contained herein is provided in good faith and is believed to be correct as of the date hereof.

However, Birchwood Laboratories, Inc. makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular period.

Accordingly, Birchwood Laboratories, Inc. will not be responsible for damages of any kind resulting from the use of or reliance upon such information. **NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS.** The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

FOR ASSISTANCE WITH PLACING ORDERS:

- Product Pricing / Payment Terms
- Shipping and Tracing of Shipments
- Sales Rep Locations

Call our Sales Department (952) 937-7933

Or 1-800-328-6156 or Fax (952) 937-7979

FOR PRODUCT USAGE ASSISTANCE

- Questions on Operation of Products
- Solving Finishing Problems
- Operator Safety and Pollution Control

Call our Customer Service Desk (952) 937-7916

Or 1-800-328-6156 or Fax (952) 937-7979